




## Product data sheet

Item No. 55.504.1053.0

# Feed-through terminal WKM 4 /15/V0

Feed-through DIN rail terminal block with screw connection for mounting on TS 15, nominal cross section 4 mm², width 6 mm, color gra



Item No.	55.504.1053.0
EAN	4015573478503
Order Unit	100 Piece(s)

# Certificates / Approvals



### Technical data

### General

Nominal cross section	4 mm²
Colour	Grey
Number of levels	1
Number of clamp positions per level	2
Width/grid dimension	6 mm
Insulating housing	PA666
Inflammability class of insulation material acc. with UL94	V0
Explosion-tested version "Ex e"	Yes
Mounting method	DIN rail (top hat rail) 15 mm
Terminal blocks for electrical installations	Yes

#### Technical data

Rated current	28 A
Rated voltage	500 V
Rated impulse voltage	6 kV
Pollution degree	3
Closing plate required	Yes
Type of insulation material	Thermoplastic
Length	32 mm

## Connection Data

Connection type 1	Screw connection
Connection type 2	Screw connection
Minimum cross section solid	0.5 mm <sup>2</sup>





Maximum cross section solid	6 mm²
Minimum cross section fine stranded	0.5 mm <sup>2</sup>
Maximum cross section fine stranded	4 mm²
Wire strip length	9 mm
Torque conductor mounting	0.5 Nm

#### Technical Data UL/CSA

Cross section UL	22-10 AWG
Voltage UL	600 V
Current factory wiring	30 A
Current field wiring	30 A
Cross section CSA	20-10 AWG
Voltage CSA	600 V
Current CSA	37 A

## Technical drawing

