


Product data sheet

Item No. 55.504.9153.0

Earth terminal WKM 4 SL / 15 / V0

Ground DIN rail terminal block with screw connection for mounting on TS 15, nominal cross section 4 mm², width 6 mm, color green/yel low



Item No.	55.504.9153.0
EAN	4015573210424
Order Unit	100 Piece(s)

Certificates / Approvals



Technical data

Note

Remark to rated voltage	No declaration for CSA/VDE
Remark to rated current	No declaration for CSA/VDE

General

Nominal cross section	4 mm ²
Colour	Green/yellow
Number of levels	1
Number of clamp positions per level	2
Width/grid dimension	6 mm
Insulating housing	PA666
Inflammability class of insulation material acc. with UL94	V0
Mounting method	DIN rail (top hat rail) 15 mm
Terminal blocks for electrical installations	Yes

Technical data

Rated impulse voltage	6 kV
Pollution degree	3
Closing plate required	Yes
Type of insulation material	Thermoplastic
Length	31.6 mm

Connection Data

Connection type 1	Screw connection
Connection type 2	Screw connection

Minimum cross section solid	0.5 mm ²
Maximum cross section solid	6 mm ²
Minimum cross section fine stranded	0.5 mm ²
Maximum cross section fine stranded	4 mm ²
Wire strip length	9 mm
Torque conductor mounting	0.5 Nm
Torque rail mounting	0,5

Technical Data UL/CSA

Cross section UL	22-14 AWG
Voltage UL	300 V
Current factory wiring	30 A
Current field wiring	30 A
Cross section CSA	22-10 AWG

Technical drawing

