


Product data sheet

Item No. 56.702.7053.0

Multi-tier terminal WKF 1,5 E / 35

Multi-tier terminal block with spring clamp connection for mounting on TS 35, nominal cross section 1.5 mm<sup>2</sup>, width 5 mm, color gray



Item No.	56.702.7053.0
EAN	4015573462465
Order Unit	100 Piece(s)

Certificates / Approvals



Technical data

General

Nominal cross section	1.5 mm <sup>2</sup>
Colour	Grey
Number of levels	2
Number of clamp positions per level	2
Width/grid dimension	5 mm
Insulating housing	PA666
Inflammability class of insulation material acc. with UL94	V0
Explosion-tested version "Ex e"	No
Mounting method	DIN rail (top hat rail) 35/7.5 mm
Terminal blocks for electrical installations	Yes

Technical data

Rated current	17.5 A
Rated voltage	400 V
Rated impulse voltage	6 kV
Pollution degree	3
Closing plate required	Yes
Type of insulation material	Thermoplastic
Length	83.4 mm

Connection Data


Connection type 1	Tension clamp connection
Connection type 2	Tension clamp connection
Minimum cross section solid	0.13 mm <sup>2</sup>

Maximum cross section solid	2.5 mm <sup>2</sup>
Minimum cross section fine stranded	0.13 mm <sup>2</sup>
Maximum cross section fine stranded	1.5 mm <sup>2</sup>
Wire strip length	8 mm

**Technical Data UL/CSA**

Cross section UL	30-14 AWG
Voltage UL	300 V
Current factory wiring	15 A
Current field wiring	15 A
Cross section CSA	30-14 AWG
Voltage CSA	600 V
Current CSA	15 A

Technical drawing



Weitere Daten siehe Katalog  
further data see catalog

Freitoleranz nach DIN		CAD - Zeichnung, keine manuellen Änderungen			i.Verwendung: -		Bl.: 1 von 1		
Maßstab		Werkstoff und Oberfläche:		2002	Tag	Name		Zeichnung Nr.	
1:1				Entworfen	26.09.	Schneiderb.		56.702.7053.0 01K	
				Geprüft	-	-		Index	
				Normgepr.	-	-		Ersatz für: -	
Buchstabe		Datum / Blatt		Typ		Benennung			
Änderung				WKF 1,5 E		ETAGENKLEMME			
				/35		double deck terminal			

A
1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
M1
M2
M3
L
G
i
11.1
12.1
1.1

