




Product data sheet

Item No. 56.706.9053.0

Earth terminal WKF 6 SL/35

Ground DIN rail terminal block with spring clamp connection for mounting on TS 35, nominal cross section 6 mm², width 8 mm, color green/yellow



| Item No. | 56.706.9053.0 |
|------------|---------------|
| EAN | 4015573501683 |
| Order Unit | 100 Piece(s) |

Certificates / Approvals



Technical data

| Nominal cross section | 6 mm ² |
|--|-----------------------------------|
| Colour | Green/yellow |
| Number of levels | 1 |
| Number of clamp positions per level | 2 |
| Width/grid dimension | 8 mm |
| Insulating housing | PA666 |
| Inflammability class of insulation material acc. with UL94 | V0 |
| Explosion-tested version "Ex e" | Yes |
| Mounting method | DIN rail (top hat rail) 35/7.5 mm |
| Terminal blocks for electrical installations | Yes |
| Technical data | |
| Rated impulse voltage | 8 kV |
| Pollution degree | 3 |
| Closing plate required | No |
| Type of insulation material | Thermoplastic |
| Length | 61 mm |
| Connection Data | |
| Connection Data | |

| Connection type 1 | Tension clamp connection |
|-------------------------------------|--------------------------|
| Connection type 2 | Tension clamp connection |
| Minimum cross section solid | 0.5 mm² |
| Maximum cross section solid | 6 mm² |
| Minimum cross section fine stranded | 0.5 mm ² |





| Maximum cross section fine stranded | 6 mm ² |
|-------------------------------------|-------------------|
| Wire strip length | 12 mm |
| | |
| Technical Data UL/CSA | |
| Cross section UL | 24-8 AWG |
| Cross section CSA | 20-8 AWG |

Technical drawing

