




Product data sheet

Item No. 57.404.7055.0

Multi-tier terminal WK 4E/U /V0

Multi-tier terminal block with screw connection for mounting on TS 35 and TS 32, nominal cross section 4 mm², width 6 mm, color gray



Item No.	57.404.7055.0
EAN	4015573527362
Order Unit	100 Piece(s)

Certificates / Approvals



Technical data

Genera	l

Nominal cross section	4 mm ²	
Colour	Grey	
Number of levels	2	
Number of clamp positions per level	2	
Width/grid dimension	6 mm	
Insulating housing	PA666	
Inflammability class of insulation material acc. with UL94	VO	
Explosion-tested version "Ex e"	No	
Mounting method	DIN rail (top hat rail)/G-rail	
Terminal blocks for electrical installations	No	
Technical data		
Rated current	32 A	
Rated voltage	400 V	
Rated impulse voltage	6 kV	
Pollution degree	3	
Closing plate required	Yes	
Type of insulation material	Thermoplastic	
Length	61.6 mm	
Connection Data		
Connection type 1	Screw connection	
Connection type 2	Screw connection	





Maximum cross section solid	4 mm ²
Minimum cross section fine stranded	0.5 mm ²
Maximum cross section fine stranded	4 mm ²
Wire strip length	9 mm
Torque conductor mounting	0.5 Nm

Technical Data UL/CSA

Cross section UL	22-10 AWG
Voltage UL	300 V
Current factory wiring	20 A
Current field wiring	20 A
Cross section CSA	20-12 AWG
Voltage CSA	300 V
Current CSA	10 A

Technical drawing

