




Product data sheet

Item No. 57.504.4055.0

Fuse terminal WK 4 TKG/U /V0

Disconnect block for fuse holder,component plug and fuse disconnect lever with screw connection for mounting on TS 35 and TS 32, no minal cross section 4 mm², width 6 mm, color gray



Item No.	57.504.4055.0
EAN	4015573527188
Order Unit	100 Piece(s)

Certificates / Approvals



Technical data

Note

Note		
Remark to rated current	Note fuse insert	
Integrated test socket	No	
General		
Nominal cross section	4 mm ²	
Colour	Grey	
Number of levels	1	
Number of clamp positions per level	2	
Width/grid dimension	6 mm	
Insulating housing	PA666	
Inflammability class of insulation material acc. with UL94	VO	
Mounting method	DIN rail (top hat rail)/G-rail	
Terminal blocks for electrical installations	No	
Technical data		
Rated voltage	800 V	
Rated impulse voltage	8 kV	
Pollution degree	3	
Closing plate required	Yes	
Type of insulation material	Thermoplastic	
Length	48 mm	
Connection Data		
Opening the target	O server a strike strik	

Connection type 1 Screw connection





Connection type 2	Screw connection
Minimum cross section solid	0.5 mm²
Maximum cross section solid	6 mm²
Minimum cross section fine stranded	0.5 mm ²
Maximum cross section fine stranded	4 mm ²
Wire strip length	9 mm
Torque conductor mounting	0.5 Nm

Technical Data UL/CSA

Cross section UL	22-10 AWG
Voltage UL	300 V
Current factory wiring	10 A
Current field wiring	10 A
Cross section CSA	20-10 AWG
Voltage CSA	250 V
Current CSA	6.3 A

Technical drawing

