


Product data sheet

Item No. 57.504.5255.0

Multi-tier terminal WK 4/D EU/V0

Multi-tier terminal block with screw connection for mounting on TS 35 and TS 32, nominal cross section 4 mm², width 6 mm, color gray



Item No.	57.504.5255.0
EAN	4015573504110
Order Unit	100 Piece(s)

Certificates / Approvals



Technical data

Note

Remark to rated voltage	500V/6kV/3 with separating plate
-------------------------	----------------------------------

General

Nominal cross section	4 mm ²
Colour	Grey
Number of levels	2
Number of clamp positions per level	2
Width/grid dimension	6 mm
Insulating housing	PA666
Inflammability class of insulation material acc. with UL94	V0
Explosion-tested version "Ex e"	Yes
Mounting method	DIN rail (top hat rail)/G-rail
Terminal blocks for electrical installations	Yes

Technical data

Rated current	32 A
Rated voltage	320 V
Rated impulse voltage	4 kV
Pollution degree	3
Closing plate required	Yes
Type of insulation material	Thermoplastic
Length	77 mm

Connection Data

Connection type 1	Screw connection
Connection type 2	Screw connection
Minimum cross section solid	0.5 mm ²
Maximum cross section solid	6 mm ²
Minimum cross section fine stranded	0.5 mm ²
Maximum cross section fine stranded	4 mm ²
Wire strip length	9 mm
Torque conductor mounting	0.5 Nm

Technical Data UL/CSA

Cross section UL	22-10 AWG
Voltage UL	300 V
Current factory wiring	30 A
Current field wiring	30 A
Cross section CSA	20-12 AWG
Voltage CSA	600 V
Current CSA	30 A

Technical drawing

