




Product data sheet

Item No. 57.597.0155.6

Feed-through terminal WKN 150/ U BLUE /V0

Feed-through DIN rail terminal block with screw connection for mounting on TS 35 and TS 32, nominal cross section 150 mm², width 28 mm, color blue



Item No.	57.597.0155.6
EAN	4015573488038
Order Unit	10 Piece(s)

Certificates / Approvals



Technical data

General

Nominal cross section	150 mm ²
Colour	Blue
Number of levels	1
Number of clamp positions per level	2
Width/grid dimension	28 mm
Insulating housing	PA666
Inflammability class of insulation material acc. with UL94	V0
Explosion-tested version "Ex e"	Yes
Mounting method	DIN rail (top hat rail)/G-rail
Terminal blocks for electrical installations	No

Technical data

Rated current	309 A
Rated voltage	1000 V
Rated impulse voltage	8 kV
Pollution degree	3
Closing plate required	No
Type of insulation material	Thermoplastic
Length	96 mm

Connection Data

Connection type 1	Screw connection
Connection type 2	Screw connection
Minimum cross section fine stranded	35 mm²





Maximum cross section fine stranded	150 mm ²
Minimum cross section stranded	35 mm ²
Maximum cross section stranded	185 mm²
Wire strip length	30 mm
Torque conductor mounting	10 Nm

Technical Data UL/CSA

Cross section UL	2/0 AWG - 350 kcmil
Voltage UL	600 V
Current factory wiring	335 A
Current field wiring	335 A
Cross section CSA	2/0 AWG - 350 kcmil
Voltage CSA	1000 V
Current CSA	365 A

Technical drawing

