

Product data sheet

Item No. 92.030.2053.0

Distributor GST18I3V 2P1K V WS

Luminaire connection TT, GST18i3, 3 pole, 1 input, 1 output, 250 V, 20 A with integrated lamp connector for internal wiring of lamps, colour of coding: white, colour of housing: white



Item No.	92.030.2053.0
EAN	4015573634510
Order Unit	100 Piece(s)

Certificates / Approvals



Technical data

General

Rated current	20 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Pollution degree	2
Mechanical coding	Code 1
Lockable	Yes
Color of coding/ contact carrier	White
Marking of poles	L, N, PE

Model

Number of inputs	1
Number of outputs	2
Type of fastening	Yes
Degree of protection (IP)	IP20
Type of distributor	Integrated lamp connector

Material

Housing material	Polyamide
------------------	-----------

Halogen free	Yes
Contact material	CuZn
Insulation components continuous temperature	100 °C
Surface finish	Tin-plated

Dimensions

Length	63 mm
Width	36.5 mm
Height	34.5 mm

Technical drawing

Einrastbolz für Blechdicken von 0,40 mm bis 0,60 mm
for sheet metal thickness of 0,40 mm to 0,60 mm

BLECHAUSSCHNITT
sheet metal cut-out

Im Bereich des Blechausschnittes Unlaufend 20mm
within the range of sheet metal cut-out (circulating 20mm)

Beispiel für Materialdicke
example for material thickness
Blechdicke / plate thickness = 0,60 mm
Lack / lacquer = max. 0,05 mm

T_VERTEILER_MIT_KLEMME
250V AC 20A

Freifahreranzack / **ModStab** / **Werkstoff und Oberfläche:** / **250V** / **Tag** / **Name** / **Zeichnung Nr.** / **92.030.2053.0 01K a** / **Index**

Änderung / **Werkstoff** / **Erwartetes Herstell.** / **Kurz Nr.** / **Benennung** / **Ersatz für:**

wieland
Stahlblech-Verbindungen

0203030010_02030300 laut 2011-06-03/01/05/11/00