



Product data sheet

Item No. 92.031.8758.0

Female connector GST18I3S B1 R V WS

Device connectors, snap-in panel mount, GST18i3, 3 pole, female, screw connection, 250 V, 20 A, material thickness 0,5 - 1,5 mm, colour of coding: white



Item No.	92.031.8758.0
EAN	4015573455559
Order Unit	100 Piece(s)



Technical data

General Rated current 20 A Rated voltage 250 V Pollution degree 2 Mechanical coding Code 1 Rated impulse voltage 4 kV Lockable Yes Color of coding/ contact carrier White L, N, PE Marking of poles

Connection Data

Cross section solid	4 mm ²
Cross section solid 2	0.75 mm²
Connection cross section stranded (max.)	4 mm ²
Cross section stranded 2	0.75 mm ²
Terminations per pole	1
Wire strip length	9 mm





Model

Model	female
Connection type	Screw connection
Angle of plug	Straight
Degree of protection (IP)	IP20
Remark to type of connection	Fine stranded wires 4 mm ² only without ferrules
Thickness of housings (electrical device) 2	0.5 mm
Thickness of housings (electrical device)	1.5 mm
Built-in component	Snap-in

Material

Housing material	Polyamide
Halogen free	Yes
Contact material	CuZn
Insulation components continous temperature	100 °C
Surface finish	Tin-plated

Dimensions

Length	30.3 mm
Width	32.8 mm
Height	21 mm

Technical drawing

