

Product data sheet

Item No. 92.032.7658.0

Male connector GST18I3F S2 REV WS

Device connectors, snap-in panel mount, GST18i3, 3 pole, male, spring clamp connection, 250 V, 20 A, material thickness 1,5 - 2,5 mm, colour of coding: white



Item No.	92.032.7658.0
EAN	4015573583887
Order Unit	100 Piece(s)

Certificates / Approvals



Technical data

General

Rated current	20 A
Rated voltage	250 V
Pollution degree	2
Mechanical coding	Code 1
Rated impulse voltage	4 kV
Lockable	Yes
Color of coding/ contact carrier	White
Marking of poles	L, N, PE

Connection Data

Cross section solid	2.5 mm²
Cross section solid 2	0.5 mm²
Connection cross section stranded (max.)	1.5 mm²
Cross section stranded 2	0.5 mm²
Terminations per pole	2
Wire strip length	9 mm

Model

Model	male
Connection type	Spring force
Angle of plug	Straight
Degree of protection (IP)	IP20
Remark to type of connection	Fine stranded and stranded conductors require cable end sleeve
Thickness of housings (electrical device) 2	1.5 mm
Thickness of housings (electrical device)	2.5 mm
Built-in component	Snap-in

Material

Housing material	Polyamide
Halogen free	Yes
Contact material	CuZn
Insulation components continuous temperature	100 °C
Surface finish	Silver-plated

Dimensions

Length	37.5 mm
Width	32.8 mm
Height	17.5 mm

Technical drawing

