

Product data sheet

Item No. 92.051.9658.1

Female connector GST18I5F B2 R V SW

Device connectors, snap-in panel mount, GST18i5, 5 pole, female, spring clamp connection, 250/400 V, 20 A, material thickness 0,5 - 1,5 mm, colour of coding: black



Item No.	92.051.9658.1
EAN	4015573399730
Order Unit	100 Piece(s)

Certificates / Approvals



Technical data

General

Rated current	20 A
Rated voltage	250 V
Rated voltage 2	400 V
Pollution degree	2
Mechanical coding	Code 1
Rated impulse voltage	4 kV
Lockable	Yes
Color of coding/ contact carrier	Black
Marking of poles	3, N, PE, 2, 1

Connection Data

Cross section solid	2.5 mm ²
Cross section solid 2	0.5 mm ²
Connection cross section stranded (max.)	1.5 mm ²
Cross section stranded 2	0.5 mm ²
Terminations per pole	2
Wire strip length	9 mm



Model

Model	female
Connection type	Spring force
Angle of plug	Straight
Degree of protection (IP)	IP20
Remark to type of connection	Fine stranded and stranded conductors require cable end sleeve
Thickness of housings (electrical device) 2	0.5 mm
Thickness of housings (electrical device)	1.5 mm
Built-in component	Snap-in

Material

Housing material	Polyamide
Halogen free	Yes
Contact material	CuZn
Insulation components continuous temperature	100 °C
Surface finish	Silver-plated

Dimensions

Length	38 mm
Width	52.3 mm
Height	18.5 mm

Technical drawing

Gehäuseausschnitt
Materialstärke 0,5 - 1,5 mm
Section of housing
Material thickness 0,5 - 1,5 mm

Teilenummer part-no.
92.051.9658.0
92.051.9658.1

Farbe colour
weiß/white
schwarz/black

Typ type
GST1815F B2 R V WS
GST1815F B2 R V SW

Material
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100

Wieland
Wieland Electric
Wieland Electric

FEMALE CONNECTOR BUCHSENTEIL
Federkraftanschl./spring loaded, Snap-in
250/400V AC 20A 2,3mm

001-FEM-08/916