

Product data sheet

Item No. 92.207.4000.1

Cable assembly GST1814KSBS 15E 40SW

geis® Extension cable female - male; length: 4m; type GST1814; 4-pole; 250/400 V / 16 A; colour of coding: black with black strain-relief; cable : H05VV-F 4G1,5, colour: black, fire class Eca



Item No.	92.207.4000.1
EAN	4015573479784
Order Unit	15 Piece(s)

Certificates / Approvals



Technical data

General

Rated current	16 A
Rated voltage	250 V
Rated voltage 2	400 V
Rated impulse voltage	4 kV
Pollution degree	2
Mechanical coding	Code 1
Lockable	Yes
Color of coding/ contact carrier	Black
Marking of poles	2, N, PE, 1
Color of housing inclusive strain relief	Black

Model

Nominal cross section conductor	1.5 mm <sup>2</sup>
Degree of protection (IP)	IP20
Cable type	H05VV-F
Cable colour	Black
Cable diameter	9.2 mm
Version of cable	Female - male



Type of cord set	Connecting cable
Version cable end 1	GST18i4 female
Version cable end 2	GST18i4 plug

**Material**

Surface finish	Tin-plated
Halogen free	No
Continuous temperature of cable	70 °C
Insulation components continuous temperature	100 °C
Fire class	Eca

**Dimensions**

Total length	4 m
--------------	-----

**Technical drawing**

**Pol / Aderfarbe / pole / colour of core**

L1	braun / brown
⊕	grün-gelb / green-yellow
N	blau / blue
L2	schwarz / black

**.F Farbe / colour**

Farbe / colour	Codierung Buchse / Female	Codierung Stecker / male	Kabelfarbe / cable colour	Zugentlastungsfarbe/strain relief colour
.1 schwarz / black	2 N PE 1	1 PE N 2	schwarz / black	schwarz / black
.2 weiß / white	2 N PE 1	1 PE N 2	weiß / white	weiß / white
.3 grau / grey	2 N PE 1	1 PE N 2	schwarz / black	schwarz / black

**Teile-Nr. / part-no.**

L	Beispiel (Farbe: schwarz) / example (colour: black)	Typ / type
92.207.XX00.F	XX in dm-Schritten	GST18i4KSBS 15 10SW
U2.207.XX00.F	XX in m-Schritten	GST18i4KSBS 15 X10SW

**92.207.1000.1 = 10dm/L= 1000mm**  
**U2.207.1200.1 = 12 m/L=12000mm**

**Typ/type: GST18i4KSBS 15**  
 SW = schwarz/black  
 WS = weiß/white  
 GR01 = grau/grey

**Weitere Daten siehe Katalog / further data see catalog**

**PRE-ASSEMBLED CABLE KONFEKT-LEITUNG**  
 Buchse/female - Stecker/male 1,5mm  
 Schraubanschluss/screw connection 250V