

Product data sheet

Item No. 92.238.1004.2

Cable assembly GST18I3K1-S 25E 10WS

geis® Connection cable male - free end; length: 1m; type GST18I3; 3-pol e; 250 V / 20 A; colour of coding: white with white strain-relief; cable : H05VV-F 3G2,5, colour: white, fire class Eca



Item No.	92.238.1004.2
EAN	4015573356689
Order Unit	50 Piece(s)

Certificates / Approvals



Technical data

General

Rated current	20 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Pollution degree	2
Mechanical coding	Code 1
Lockable	Yes
Color of coding/ contact carrier	White
Marking of poles	L, N, PE
Color of housing inclusive strain relief	White

Model

Nominal cross section conductor	2.5 mm ²
Degree of protection (IP)	IP20
Wire strip length	9 mm
sheath strip length	37 mm
Preparation of conductor ends	Ultrasonically compressed wire ends
Cable type	H05VV-F
Cable colour	White



Cable diameter	10.2 mm
Version of cable	Male - free end
Type of cord set	Connection cable
Version cable end 1	GST18i3 plug
Version cable end 2	Free end

Material

Surface finish	Tin-plated
Halogen free	No
Continuous temperature of cable	70 °C
Insulation components continuous temperature	100 °C
Fire class	Eca

Dimensions

Total length	1 m
--------------	-----

Technical drawing

Steckerteil/male connector

Gesamtlänge / total length

Kabel/cable H05VV-F362,5
Farbe/colour: siehe Tabelle/see table

.F	Farbe colour	Codierung Stecker make	Kabelfarbe cable colour
.1	schwarz black	L R N	schwarz black
.2	weiß white	L R N	weiß white
.3	grau grey	L R N	schwarz black
.5	rot red	L R N	schwarz black

Teile-Nr. part-no.	L	Beispiel (Farbe: schwarz) example (colour: black)	Typ type
92.238.XX04.F	XX in dm-Schritten	92.238.1004.1 = 10dm/L = 1000mm	GST18i3K1-S 25 10SW
U2.238.XX04.F	XX in m-Schritten	U2.238.1204.1 = 12 m/L = 12000mm	GST18i3K1-S 25 X12SW

Typ/type: GST18i3K1-S 25 ..
 SW = schwarz/black
 WS = weiß/white
 GR01 = grau/grey
 RT03 = rot/red

Freiwillig nach Optional tolerance	ISO	Zielfertigung, keine parastatische Abstrahlung Target production, no parasitic radiation allowed	1. Verwendung First use	Beitrag Share	Index
/	/	Werkstoff/Material	Zielfertigung Target production	Steckerteil Connector	Steckerteil Connector
/	/	Material/Code	92.238.0204.1	Steckerteil Connector	Steckerteil Connector
/	/	Vol.	92.238.0204.1	Steckerteil Connector	Steckerteil Connector
/	/	Werkstoff/Material	92.238.0204.1	Steckerteil Connector	Steckerteil Connector
/	/	Werkstoff/Material	92.238.0204.1	Steckerteil Connector	Steckerteil Connector

PRE-ASSEMBLED CABLE
KONFEKT LEITUNG
 Stecker/male: freies Ende/Free end Impression K1
 250V AC 20A 2,5mm