

Product data sheet

Item No. 92.257.1000.1

Cable assembly GST18I5KSBS 15E 10SW

geis® Extension cable female - male; length: 1m; type GST18I5;
5-pole; 2 50/400 V / 16 A; colour of coding: black with black strain-
relief; cable : H05VV-F 5G1,5, colour: black, fire class Eca



Item No.	92.257.1000.1
EAN	4015573587908
Order Unit	30 Piece(s)

Certificates / Approvals



Technical data

General

Rated current	16 A
Rated voltage	250 V
Rated voltage 2	400 V
Rated impulse voltage	4 kV
Pollution degree	2
Mechanical coding	Code 1
Lockable	Yes
Color of coding/ contact carrier	Black
Marking of poles	3, N, PE, 2, 1
Color of housing inclusive strain relief	Black

Model

Nominal cross section conductor	1.5 mm ²
Degree of protection (IP)	IP20
Cable type	H05VV-F
Cable colour	Black
Cable diameter	10.1 mm
Version of cable	Female - male
Type of cord set	Connecting cable
Version cable end 1	GST18i5 female
Version cable end 2	GST18i5 plug

Material

Surface finish	Tin-plated
Halogen free	No
Continuous temperature of cable	70 °C
Insulation components continuous temperature	100 °C
Fire class	Eca

Dimensions

Total length	1 m
--------------	-----



Technical drawing

Buchsteil/female connector Steckerteil/male connector

Kabel/cable H05VV-F 5G1,5
Farbe/color: siehe Tabelle/see table

Gesamtlänge / total length: $L \pm 3\%$

Typ/type: GST1815KSBS 15 SW = schwarz/black
WS = weiß/white

.F	Farbe colour	Codierung •X• Buchse female	Codierung •Y• Stecker male	Kabelfarbe cable colour
.1	schwarz black	3 N PE 2 1	1 2 PE N 3	schwarz black
.2	weiß white			weiß white

Teile-Nr. part-no.	L	Beispiel (Farbe: schwarz) example (colour: black)	Type
92.257.XX00.F	XX in dm-Schritten	92.257.1000.1 = 10dm/L= 1000mm	GST1815KSBS 15 10SW
U2.257.XX00.F	XX in m-Schritten	U2.257.1200.1 = 12 m/L=12000mm	GST1815KSBS 15 X12SW

Further information: DIN 7162/Tolerance system acc. to DIN 7162. (This DIN standard describes the envelope principle. According to the envelope principle the deviations of form and position are limited by the size tolerances.)

Material: Buchsteil/Material: 2507 Kupfer / Steckerteil: Name: T

Scale: Maßstab: 1:1

Drawing No./Zeichnung Nr.: 92.257.0500.1 01K a

PRE-ASSEMBLED CABLE KONFEKTLEITUNG

Buchse/female - Stecker/male
Schraubanschluss/screw connection: 250/400V 1,5gmm

Wieland
Waldschlocher
Vertriebskompan

Änderung/Revision: 01.02.2002/01