

Product data sheet

Item No. 92.257.3004.1

Cable assembly GST18I5KS-S 15E 30SW

geis® Connection cable male - free end; length: 3m; type
GST18I5; 5-pole; 250/400 V / 16 A; colour of coding: black with
black strain-relief; cable: H05VV-F 5G1,5, colour: black, fire class
Eca



Item No.	92.257.3004.1
EAN	4015573588080
Order Unit	15 Piece(s)

Certificates / Approvals

Technical data
General

Rated current	16 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Pollution degree	2
Mechanical coding	Code 1
Lockable	Yes
Color of coding/ contact carrier	Black
Marking of poles	3, N, PE, 2, 1
Color of housing inclusive strain relief	Black

Model

Nominal cross section conductor	1.5 mm ²
Degree of protection (IP)	IP20
Wire strip length	9 mm
sheath strip length	35 mm
Preparation of conductor ends	Ultrasonically compressed wire ends
Cable type	H05VV-F
Cable colour	Black
Cable diameter	10.1 mm
Version of cable	Male - free end
Type of cord set	Connection cable
Version cable end 1	GST18/5 plug
Version cable end 2	Free end

Material

Surface finish	Tin-plated
Halogen free	No
Continuous temperature of cable	70 °C
Insulation components continuous temperature	100 °C
Fire class	Eca

Dimensions

Total length	3 m
--------------	-----

