

Product data sheet

Item No. 92.257.5004.1

Cable assembly GST18I5KS-S 15E 50SW

geis® Connection cable male - free end; length: 5m; type
GST18I5; 5-pole; 250/400 V / 16 A; colour of coding: black with
black strain-relief; cable: H05VV-F 5G1,5, colour: black, fire class
Eca



Item No.	92.257.5004.1
EAN	4015573588103
Order Unit	10 Piece(s)

Certificates / Approvals

Technical data
General

Rated current	16 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Pollution degree	2
Mechanical coding	Code 1
Lockable	Yes
Color of coding/ contact carrier	Black
Marking of poles	3, N, PE, 2, 1
Color of housing inclusive strain relief	Black

Model

Nominal cross section conductor	1.5 mm ²
Degree of protection (IP)	IP20
Wire strip length	9 mm
sheath strip length	35 mm
Preparation of conductor ends	Ultrasonically compressed wire ends
Cable type	H05VV-F
Cable colour	Black
Cable diameter	10.1 mm
Version of cable	Male - free end
Type of cord set	Connection cable
Version cable end 1	GST18/5 plug
Version cable end 2	Free end

Material

Surface finish	Tin-plated
Halogen free	No
Continuous temperature of cable	70 °C
Insulation components continuous temperature	100 °C
Fire class	Eca

Dimensions

Total length	5 m
--------------	-----

Technical drawing

Kabel/cable H05VV-F 5G 1,5
Farbe/color: siehe Tabelle/see table

SteckerTeil/male connector

Gesamtlänge/total length

Typ/type: GST1815KS-S 15 .. SW = schwarz/black
WS = weiß/white

.F	Farbe colour	Codierung Stecker male	Kabelfarbe cable colour
.1	schwarz black	1 2 PE N 3	schwarz black
.2	weiß white		weiß white

Teile-Nr. part-no.	L	Beispiel (Farbe: schwarz) example (colour: black)	Typ type
92.257.XX04.F	XX in dm-Schritten	92.257.1004.1 = 10dm/L= 1000mm	GST1815KS-S 15 10SW
U2.257.XX04.F	XX in m-Schritten	U2.257.1204.1 = 12 m/L=12000mm	GST1815KS-S 15 X12SW

Steckertoleranz nach General tolerance: /

Material: Weichstahl/Material: 2024-Typ/Detail: Name: T Zeichnung Nr./Drawing No. 92.257.0504.1 01K g

Wieland
Waldmühle
Vertriebskompan

PRE-ASSEMBLED CABLE
KONFEKT_LEITUNG
Stecker/Note - free end/free end and
Schraubenschluß/screw connection: 250V/400V 1,5qmm