

Product data sheet

Item No. 92.258.1003.9

**Cable assembly GST1815KSB- 25E 10PB02**

geis® Connection cable female - free end; length: 1m; type GST1815; 5-p ole; 250/400 V / 20 A; colour of coding: pastel blue with black strain-r elief; cable: H05VV-F 5G2,5, colour: black, fire class Eca



Item No.	92.258.1003.9
EAN	4049644007293
Order Unit	30 Piece(s)

**Certificates / Approvals**

**Technical data**
**General**

Rated current	20 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Pollution degree	2
Mechanical coding	Code 2
Lockable	Yes
Color of coding/ contact carrier	Pastel blue
Marking of poles	L, N, PE, D2, D1
Color of housing inclusive strain relief	Black

**Model**

Nominal cross section conductor	2.5 mm <sup>2</sup>
Degree of protection (IP)	IP20
Wire strip length	9 mm
sheath strip length	35 mm
Preparation of conductor ends	Ultrasonically compressed wire ends
Cable type	H05VV-F
Cable colour	Black
Cable diameter	12.1 mm
Version of cable	Female - free end
Type of cord set	Connection cable
Version cable end 1	GST18/5 female
Version cable end 2	Free end

**Material**

Surface finish	Tin-plated
Halogen free	No
Continuous temperature of cable	70 °C
Insulation components continuous temperature	100 °C
Fire class	Eca

**Dimensions**

Total length	1 m
--------------	-----