

Product data sheet

Item No. 92.258.1004.9

Cable assembly GST1815KS-S 25E 10PB02

geis® Connection cable male - free end; length: 1m; type GST1815; 5-pol e; 250/400 V / 20 A; colour of coding: pastel blue with black strain-relief; cable: H05VV-F 5G2,5, colour: black, fire class Eca



| | |
|------------|---------------|
| Item No. | 92.258.1004.9 |
| EAN | 4015573993679 |
| Order Unit | 30 Piece(s) |

Certificates / Approvals

Technical data
General

| | |
|--|------------------|
| Rated current | 20 A |
| Rated voltage | 250 V |
| Rated impulse voltage | 4 kV |
| Pollution degree | 2 |
| Mechanical coding | Code 2 |
| Lockable | Yes |
| Color of coding/ contact carrier | Pastel blue |
| Marking of poles | L, N, PE, D2, D1 |
| Color of housing inclusive strain relief | Black |

Model

| | |
|---------------------------------|-------------------------------------|
| Nominal cross section conductor | 2.5 mm ² |
| Degree of protection (IP) | IP20 |
| Wire strip length | 9 mm |
| sheath strip length | 35 mm |
| Preparation of conductor ends | Ultrasonically compressed wire ends |
| Cable type | H05VV-F |
| Cable colour | Black |
| Cable diameter | 12.1 mm |
| Version of cable | Male - free end |
| Type of cord set | Connection cable |
| Version cable end 1 | GST18/5 plug |
| Version cable end 2 | Free end |

Material

| | |
|--|------------|
| Surface finish | Tin-plated |
| Halogen free | No |
| Continuous temperature of cable | 70 °C |
| Insulation components continuous temperature | 100 °C |
| Fire class | Eca |

Dimensions

| | |
|--------------|-----|
| Total length | 1 m |
|--------------|-----|