

Product data sheet

Item No. 92.258.3003.9

Cable assembly GST1815KSB- 25E 30PB02

geis® Connection cable female - free end; length: 3m; type GST1815; 5-pole; 250/400 V / 20 A; colour of coding: pastel blue with black strain-relief; cable: H05VV-F 5G2,5, colour: black, fire class Eca



Item No.	92.258.3003.9
EAN	4049644007309
Order Unit	15 Piece(s)

Certificates / Approvals



Technical data

General

Rated current	20 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Pollution degree	2
Mechanical coding	Code 2
Lockable	Yes
Color of coding/ contact carrier	Pastel blue
Marking of poles	L, N, PE, D2, D1
Color of housing inclusive strain relief	Black

Model

Nominal cross section conductor	2.5 mm ²
Degree of protection (IP)	IP20
Wire strip length	9 mm
sheath strip length	35 mm
Preparation of conductor ends	Ultrasonically compressed wire ends
Cable type	H05VV-F
Cable colour	Black
Cable diameter	12.1 mm
Version of cable	Female - free end
Type of cord set	Connection cable
Version cable end 1	GST18/5 female
Version cable end 2	Free end

Material

Surface finish	Tin-plated
Halogen free	No
Continuous temperature of cable	70 °C
Insulation components continuous temperature	100 °C
Fire class	Eca

Dimensions

Total length	3 m
--------------	-----