

Product data sheet

Item No. 92.258.6000.9

Cable assembly GST1815KSBS 25E 60PB02

geis® Extension cable female - male; length: 6m; type GST1815;
5-pole; 2 50/400 V / 20 A; colour of coding: pastel blue with black
strain-relief; cable: H05VV-F 5G2,5, colour: black, fire class Eca



Item No.	92.258.6000.9
EAN	4049644007187
Order Unit	5 Piece(s)

Certificates / Approvals

Technical data
General

Rated current	20 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Pollution degree	2
Mechanical coding	Code 2
Lockable	Yes
Color of coding/ contact carrier	Pastel blue
Marking of poles	L, N, PE, D2, D1
Color of housing inclusive strain relief	Black

Model

Nominal cross section conductor	2.5 mm ²
Degree of protection (IP)	IP20
Cable type	H05VV-F
Cable colour	Black
Cable diameter	12.1 mm
Version of cable	Female - male
Type of cord set	Connecting cable
Version cable end 1	GST18i5 female
Version cable end 2	GST18i5 plug

Material

Surface finish	Tin-plated
Halogen free	No
Continuous temperature of cable	70 °C
Insulation components continuous temperature	100 °C
Fire class	Eca

Dimensions

Total length	6 m
--------------	-----



Technical drawing

Weitere Daten siehe Katalog
further data see catalog

Kabel/cable H05VV-F 5G 2,5
Farbe/colour: schwarz/black

Typ/type: GST1815KSBS 25 ..PB02

Teile-Nr. part-no.	L	Beispiel (Farbe: pastellblau) example (colour: pastel blue)	Typ type
92.258.XX00.9	XX in dm-Schritten	92.258.1000.9 = 10dm/L= 1000mm	GST1815KSBS 25 10PB02
U2.258.XX00.9	XX in m-Schritten	U2.258.1200.9 = 12 m/L=12000mm	GST1815KSBS 25 K12PB02

Einsatz-Farbe insert colour	Codierung *X* Buchse female	Codierung *Y* Stecker male	Kabelfarbe cable colour		
Pastellblau pastel blue	L N PE D2 D1	D1 D2 PE N L	schwarz black		

Einsatz-Farbe insert colour	Codierung *X* Buchse female	Codierung *Y* Stecker male	Kabelfarbe cable colour		
Pastellblau pastel blue	L N PE D2 D1	D1 D2 PE N L	schwarz black		

Einsatz-Farbe insert colour	Codierung *X* Buchse female	Codierung *Y* Stecker male	Kabelfarbe cable colour		
Pastellblau pastel blue	L N PE D2 D1	D1 D2 PE N L	schwarz black		