



#### Product data sheet

Item No. 92.932.3053.0

Male connector with strain relief GST18I3S S1 ZR1 WS

Connector GST18i3, 3 pole, male, screw connection, 250 V, 20 A, colour of coding: white, colour of housing: white



Item No.	92.932.3053.0
EAN	4015573721869
Order Unit	50 Piece(s)

# Certificates / Approvals







### Technical data

General	
Rated current	20 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Strain relief	Yes
Pollution degree	2
Mechanical coding	Code 1
Lockable	Yes
Color of coding/ contact carrier	White
Marking of poles	L, N, PE
Color of housing inclusive strain relief	White

## Connection Data

Cable diameter	10.5 mm
Cable diameter 2	6.5 mm
Cross section solid	2.5 mm <sup>2</sup>
Cross section solid 2	0.75 mm²
Connection cross section stranded max.	2.5 mm <sup>2</sup>
Cross section stranded 2	0.75 mm²





Terminations per pole	1	
Model		
Model	male	
Connection type	Screw connection	
Degree of protection (IP)	IP20	
Material Material		
Housing material	Polyamide	
Halogen free	Yes	
Contact material	CuZn	
Insulation components continous temperature	100 °C	
Surface finish	Tin-plated	
Dimensions		
Length	69.4 mm	
Width	28.2 mm	
Height	12.6 mm	

