



Product data sheet

Item No. 92.933.0153.0

Female connector with strain relief GST18I3F B2 ZR1 GR01

Connector GST18i3, 3 pole, female, spring clamp connection, 250 V, 20 A, colour of coding: pepple grey, colour of housing: black



Item No.	92.933.0153.0
EAN	4015573410534
Order Unit	50 Piece(s)

Certificates / Approvals



Technical data

General

Rated current	20 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Strain relief	Yes
Pollution degree	2
Mechanical coding	Code 2
Lockable	Yes
Color of coding/ contact carrier	Pebble gray
Marking of poles	L, N, PE
Color of housing inclusive strain relief	Black

Cable diameter	10.3 mm
Cable diameter 2	7.8 mm
Cross section solid	2.5 mm ²
Cross section solid 2	0.5 mm ²
Connection cross section stranded max.	1.5 mm ²
Cross section stranded 2	0.5 mm ²

💎 wieland



Terminations per pole	2	
Model		
Model	female	
Connection type	Spring force	
Degree of protection (IP)	IP20	
Remark to type of connection	Fine stranded and stranded conductors require cable end sleeve	
Material		

Housing material	Polyamide
Halogen free	Yes
Contact material	CuZn
Insulation components continous temperature	100 °C
Surface finish	Tin-plated

Dimensions

Length	75 mm
Width	32.5 mm
Height	15.5 mm

Technical drawing

