

Product data sheet

Item No. 92.944.3053.1

Male connector with strain relief GST18i4S S1 ZR1 SW

Connector GST18i4, 4 pole, male, screw connection, 250 V, 20 A, colour of coding: black, colour of housing: black



Item No.	92.944.3053.1
EAN	4015573785625
Order Unit	50 Piece(s)

Certificates / Approvals



Technical data

General

Rated current	20 A
Rated voltage	250 V
Rated voltage 2	400 V
Rated impulse voltage	4 kV
Strain relief	Yes
Pollution degree	2
Mechanical coding	Code 1
Lockable	Yes
Color of coding/ contact carrier	Black
Marking of poles	2, N, PE, 1
Color of housing inclusive strain relief	Black

Connection Data

Cable diameter	12 mm
Cable diameter 2	6.5 mm
Cross section solid	2.5 mm ²
Cross section solid 2	0.75 mm ²
Connection cross section stranded max.	2.5 mm ²

Cross section stranded 2	0.75 mm ²
Terminations per pole	2

Model

Model	male
Connection type	Screw connection
Degree of protection (IP)	IP20

Material

Housing material	Polyamide
Halogen free	Yes
Contact material	CuZn
Insulation components continuous temperature	100 °C
Surface finish	Tin-plated

Dimensions

Length	69.4 mm
Width	38 mm
Height	15 mm

