



Product data sheet

Item No. 93.432.2553.1

Male connector with strain relief BST14I3F S1 ZR1 MSW

Connector BST14i3, 3 pole, male, spring clamp connection, 50V/3A, color of coding: black, color of housing: black



| Item No. | 93.432.2553.1 |
|------------|---------------|
| EAN | 4015573460652 |
| Order Unit | 50 Piece(s) |

Certificates / Approvals



Technical data

General

| Rated current | 3 A |
|--|--------|
| Rated voltage | 50 V |
| Rated impulse voltage | 0.8 kV |
| Strain relief | Yes |
| Pollution degree | 2 |
| Mechanical coding | Code 3 |
| Lockable | Yes |
| Color of coding/ contact carrier | Black |
| Marking of poles | 1+, 2- |
| Color of housing inclusive strain relief | Black |

Connection Data

| Cable diameter | 6.5 mm |
|-----------------------|--------|
| Cable diameter 2 | 5.5 mm |
| Terminations per pole | 1 |

Model

| Model | male |
|-------|------|
| | |





| Connection type | Spring force |
|---------------------------|--------------|
| Degree of protection (IP) | IP20 |

Material

| Housing material | Polyamide |
|---|-----------|
| Halogen free | Yes |
| Contact material | CuBe |
| Insulation components continous temperature | 100 °C |
| Surface finish | Gilt |

Dimensions

| Length | 47 mm |
|--------|---------|
| Width | 15.2 mm |
| Height | 14.4 mm |