



Product data sheet

Item No. 94.425.2030.9

Cable assembly BST14I2KFBS 50L 20PB02

gesis® Extension cable female - male; length: 2m; type BST14l2; 2-pole; $50\ V\ /\ 3$ A; colour of coding: pastel blue with black strain-relief; cable: L03VV-U 2X0,5, colour: black



| Item No. | 94.425.2030.9 |
|------------|---------------|
| EAN | 4015573802742 |
| Order Unit | 75 Piece(s) |

Certificates / Approvals

Technical data

General

| Rated current | 3 A | |
|--|-------------|--|
| Rated voltage | 50 V | |
| Rated impulse voltage | 0.8 kV | |
| Pollution degree | 2 | |
| Mechanical coding | Yes | |
| Lockable | No | |
| Color of coding/ contact carrier | Pastel blue | |
| Marking of poles | 1+, 2- | |
| Color of housing inclusive strain relief | Black | |
| | | |

Model

| Nominal cross section conductor | 0.5 mm ² |
|---------------------------------|---------------------|
| Degree of protection (IP) | IP20 |
| Cable type | L03VV-U |
| Cable colour | Black |
| Cable diameter | 4.8 mm |
| Version of cable | Female - male |
| Type of cord set | Connecting cable |
| Version cable end 1 | female |
| Version cable end 2 | male |





Material

| Surface finish | Gilt |
|---|--------|
| Halogen free | No |
| Continuous temperature of cable | 00 °C |
| Insulation components continous temperature | 100 °C |

Dimensions

| - 1 | | | |
|-----|--------------|-----|--|
| | Total length | 2 m | |
| | Total longin | 2 | |

Technical drawing

