

Product data sheet

Item No. 94.425.4034.9

Cable assembly BST14I2KF-S 50L 40PB02

geis® Connection cable male - free end; length: 4m; type BST14I2; 2-pole; 50 V / 3 A; colour of coding: pastel blue with black strain-relief; cable: L03VV-U 2X0,5, colour: black



Item No.	94.425.4034.9
EAN	4015573803015
Order Unit	30 Piece(s)

Certificates / Approvals

Technical data

General

Rated current	3 A
Rated voltage	50 V
Rated impulse voltage	0.8 kV
Pollution degree	2
Mechanical coding	Yes
Lockable	No
Color of coding/ contact carrier	Pastel blue
Marking of poles	1+, 2-
Color of housing inclusive strain relief	Black

Model

Nominal cross section conductor	0.5 mm ²
Degree of protection (IP)	IP20
Wire strip length	9 mm
sheath strip length	21 mm
Preparation of conductor ends	Other
Cable type	L03VV-U
Cable colour	Black
Cable diameter	4.8 mm
Version of cable	Male - free end



Type of cord set	Connection cable
Version cable end 1	male
Version cable end 2	Free end

Material

Surface finish	Gilt
Halogen free	No
Continuous temperature of cable	60 °C
Insulation components continous temperature	100 °C

Dimensions

Total length	4 m
--------------	-----

Technical drawing

Steckereinsatz pastellblau
plug insert pastel blue

Isoliergehäuse schwarz
insulating housing black

16
12.9
4.7
15.2
L+4

Gesamtlänge/total length = (L+50) + 3% (L < 3000mm)
Gesamtlänge/total length = (L+100) + 3% (L ≥ 3000mm)

2 Pole/2 poles

Pol	Aderfarbe
+	rot/red
-	schwarz/black

Weitere Daten siehe Katalog
further data see catalog

Teilenummer	L	Beispiel	Typ
part number		example	type
94.425.XX34.9	XX in dm-Schritten XX in dm-steps	94.425.1034.9 = 10dm /L= 1000mm	BST1412KF-S 50L 10PB02
U4.425.XX34.9	XX in m-Schritten XX in m-steps	U4.425.1234.9 = 12 m /L=12000mm	BST1412KF-S 50L X12PB02

2007 27.04. Schnitt I. T 94.425.1034.9 01K a

wieland
Niedervolt SDV - 3A 0,5 gmm --/ST
connection cable male-free end

60-FEB-08/916