



Product data sheet


Item No. 96.031.0153.0

Connector RST20I3F B2 ZR2 GR

RST 20i3/2 connector, 3 pole, female, spring clamp connection, application 250V, 20A, for cable diameters 10-14mm, coding-color light grey, color of housing light grey



Item No.	96.031.0153.0
EAN	4015573743472
Order Unit	100 Piece(s)






Technical data

General	
Rated current	20 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Strain relief	Yes
Pollution degree	3
Mechanical coding	Code 0
Lockable	Yes
Color of coding/ contact carrier	Light grey
Marking of poles	L, N, PE
Color of housing inclusive strain relief	Light grey

Connection Data

Cable diameter	14 mm
Cable diameter 2	10 mm
Cable diameter 3	14 mm
Cross section solid	2.5 mm ²
Cross section solid 2	0.5 mm ²
Connection cross section stranded max.	1.5 mm ²





Cross section stranded 2	0.5 mm ²
Terminations per pole	2
Connection cross section stranded min.	0.75 mm²
Connection cross section stranded max.	1.5 mm ²

Model

Model	female
Connection type	Spring force
Degree of protection (IP)	IP66/68 (3m;2h) /IP69

Material

Housing material	Polyamide
Halogen free	Yes
Contact material	CuZn
Insulation components continous temperature	100 °C
Surface finish	Silver-plated

Dimensions

Length	80.4 mm
Width	34.6 mm
Height	34.6 mm

Technical drawing

