

Product data sheet

Item No. 96.031.1053.0

Device connector RST20I3F B2 M01 GL

RST 20i3/2 device connection M25, 3 pole, female, spring clamp connection, application 250V, 20A, coding-color light grey, color of housing light grey



Item No.	96.031.1053.0
EAN	4015573743700
Order Unit	100 Piece(s)

Certificates / Approvals



Technical data

General

Rated current	20 A
Rated voltage	250 V
Pollution degree	3
Mechanical coding	Code 0
Rated impulse voltage	4 kV
Continuity resistor	3 mOhm
Lockable	Yes
Color of coding/ contact carrier	Light grey
Marking of poles	L, N, PE

Connection Data

Cross section solid	2.5 mm ²
Cross section solid 2	0.5 mm ²
Connection cross section stranded (max.)	1.5 mm ²
Cross section stranded 2	0.5 mm ²
Terminations per pole	2
Wire strip length	14.5 mm



Model

Model	female
Connection type	Spring force
Connecting thread metric	M25
Angle of plug	Straight
Inclination	0°
Degree of protection (IP)	IP66/68 (3m;2h) /IP69
Thickness of housings (electrical device) 2	0.5 mm
Thickness of housings (electrical device)	8 mm
Built-in component	Built-in component/connector

Material

Housing material	Polyamide
Halogen free	Yes
Contact material	CuZn
Insulation components continuous temperature	100 °C
Surface finish	Silver-plated

Dimensions

Length	46.5 mm
Width	35 mm
Height	35 mm

Technical drawing

<p>Offnungsmassbild siehe 96.031.1053.1 14K opening dimension see 96.031.1053.1 14K</p>	<p>Auslieferungszustand delivery status</p> <p>Verpackungseinheit: je 100 Stück packaging unit: per 100</p>	<p>96.031.1053.1 RST2013F B2 M01 SW Schwarz /black 96.031.1053.0 RST2013F B2 M01 GL Lichtgrau /lightgrey</p> <table border="1"> <tr> <td>Bestellnummer /Order number</td> <td>Typ /type</td> <td>Farbe /color</td> </tr> </table> <p>Weitere Daten siehe KATALOG oder eCatalog. www.wieland-electric.com Additional data see CATALOG or eCatalog. eshop.wieland-electric.com</p> <p>Tolerierung Size 120 14025 Tolerance system Size 120 14025 je 25 Statistischer und Distributionssicherheitsfaktor nach DIN 50103:2010 zur Anwendung. (This ISO-standard describes the envelope principle. According to the envelope principle the deviations of form and position are limited by the size tolerances.) Conforms with Wieland document MW 5010.010 d. (List of prohibited / declarable hazardous substances) to be declared!</p> <p>Zeichnung: kein-messeltes Androgens Tolerierung: - Blatt: 1 von 1 EAD - drawing, no manual modifications allowed First Use: -</p> <table border="1"> <tr> <td>Werkstoff/Material</td> <td>Z015</td> <td>Tag/Date</td> <td>Name</td> <td>Zeichnung Nr./Drawing No.</td> <td>Blatt/Sheet</td> </tr> <tr> <td>Herstellung/Production</td> <td>06.07.</td> <td>Höfmann</td> <td></td> <td>96.031.1053.0 13K</td> <td>1 of 1</td> </tr> </table> <p>Masse in mm/Dimensions are in mm</p> <p>Vol. nr 011./Serl. nr Ersatz für/Replacement for: -</p> <p>Index</p> <p>www.wieland.com</p> <p>BUCHSENTEIL female connector</p>	Bestellnummer /Order number	Typ /type	Farbe /color	Werkstoff/Material	Z015	Tag/Date	Name	Zeichnung Nr./Drawing No.	Blatt/Sheet	Herstellung/Production	06.07.	Höfmann		96.031.1053.0 13K	1 of 1
Bestellnummer /Order number	Typ /type	Farbe /color															
Werkstoff/Material	Z015	Tag/Date	Name	Zeichnung Nr./Drawing No.	Blatt/Sheet												
Herstellung/Production	06.07.	Höfmann		96.031.1053.0 13K	1 of 1												