



### Product data sheet

Item No. 96.031.4053.0

#### Connector RST20I3S B1 ZR1 GL

RST 20i3/2 connector, 3 pole, female, screw connection, application 250V, 20A, for cable diameters 6-10mm, coding-color light grey, color of housing light grey



Item No.	96.031.4053.0
EAN	4015573769618
Order Unit	100 Piece(s)

# Certificates / Approvals











# Technical data

#### General

Rated current	20 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Strain relief	Yes
Pollution degree	3
Mechanical coding	Code 0
Lockable	Yes
Color of coding/ contact carrier	Light grey
Marking of poles	L, N, PE
Color of housing inclusive strain relief	Light grey

# **Connection Data**

Cable diameter	10 mm
Cable diameter 2	6 mm
Cable diameter 3	10 mm
Cross section solid	6 mm²
Cross section solid 2	0.75 mm²
Connection cross section stranded max.	6 mm <sup>2</sup>





Cross section stranded 2	0.75 mm²
Terminations per pole	1
Connection cross section stranded min.	0.75 mm²
Connection cross section stranded max.	6 mm²

#### Model

Model	female
Connection type	Screw connection
Degree of protection (IP)	IP66/68 (3m;2h) /IP69

#### Material

Housing material	Polyamide
Halogen free	Yes
Contact material	CuZn
Insulation components continous temperature	100 °C
Surface finish	Silver-plated

#### Dimensions

Length	80.4 mm
Width	34.6 mm
Height	34.6 mm

### Technical drawing

