



Product data sheet

Item No. 96.031.4153.0

Connector RST20I3S B1 ZR2 GL

RST 20i3/2 connector, 3 pole, female, screw connection, application 250V, 20A, for cable diameters 10-14mm, coding-color light grey, color of housing light grey



Item No.	96.031.4153.0
EAN	4015573769632
Order Unit	100 Piece(s)

Certificates / Approvals











Technical data

General	
20 A	
250 V	
4 kV	
Yes	
3	
Code 0	
Yes	
Light grey	
L, N, PE	
Light grey	

Connection Data

Cable diameter	14 mm
Cable diameter 2	10 mm
Cable diameter 3	14 mm
Cross section solid	6 mm²
Cross section solid 2	0.75 mm²
Connection cross section stranded max.	6 mm ²





Cross section stranded 2	0.75 mm²
Terminations per pole	1
Connection cross section stranded min.	0.75 mm²
Connection cross section stranded max.	6 mm²

Model

Model	female
Connection type	Screw connection
Degree of protection (IP)	IP66/68 (3m;2h) /IP69

Material

Housing material	Polyamide
Halogen free	Yes
Contact material	CuZn
Insulation components continous temperature	100 °C
Surface finish	Silver-plated

Dimensions

Length	80.4 mm
Width	34.6 mm
Height	34.6 mm

Technical drawing

