



Product data sheet

Item No. 96.031.5054.3

Device connector RST25I3S B1 M01V GR0

RST 25i3 device connection M25, 3 pole, female, screw connection, application 250V/400V, 25A, coding-color concrete grey, color of housing black



Item No.	96.031.5054.3
EAN	4015573864085
Order Unit	100 Piece(s)

# Certificates / Approvals

### Technical data

General

Rated current	25 A
Rated voltage	250 V
Rated voltage 2	400 V
Pollution degree	3
Mechanical coding	Code 3
Rated impulse voltage	4 kV
Continuity resistor	3 mOhm
Lockable	Yes
Color of coding/ contact carrier	Concrete gray
Marking of poles	L, N, PE
Color of separate adapter (if present)	Black

**Connection Data** 

Cross section solid	6 mm <sup>2</sup>
Cross section solid 2	0.75 mm <sup>2</sup>
Connection cross section stranded (max.)	6 mm <sup>2</sup>
Cross section stranded 2	0.75 mm <sup>2</sup>
Terminations per pole	1
Wire strip length	8 mm





#### Model

Model	female
Connection type	Screw connection
Connecting thread metric	M25
Angle of plug	Straight
Inclination	0 °
Degree of protection (IP)	IP66/68 (3m;2h) /IP69
Thickness of housings (electrical device) 2	0.5 mm
Thickness of housings (electrical device)	8 mm
Built-in component	Built-in component/connector

#### Material

Housing material	Polyamide
Halogen free	Yes
Contact material	CuZn
Insulation components continous temperature	100 °C
Surface finish	Silver-plated

## Dimensions

Length	46.5 mm
Width	35 mm
Height	35 mm

### Technical drawing

