



Product data sheet

Item No. 96.032.1053.0

Device connector RST20I3F S2 M01V GL

RST 20i3/2 device connection M25, 3 pole, male, spring clamp connection, application 250V, 20A, coding-color light grey, color of housing light grey



Item No.	96.032.1053.0
EAN	4015573743724
Order Unit	100 Piece(s)

Certificates / Approvals









Technical data

General

oneral control	
20 A	
250 V	
3	
Code 0	
4 kV	
3 mOhm	
Yes	
Light grey	
L, N, PE	

Connection Data

Cross section solid	2.5 mm ²
Cross section solid 2	0.5 mm ²
Connection cross section stranded (max.)	1.5 mm ²
Cross section stranded 2	0.5 mm ²
Terminations per pole	2
Wire strip length	14.5 mm





Model

Model	male
Connection type	Spring force
Connecting thread metric	M25
Angle of plug	Straight
Inclination	0 °
Degree of protection (IP)	IP66/68 (3m;2h) /IP69
Thickness of housings (electrical device) 2	0.5 mm
Thickness of housings (electrical device)	8 mm
Built-in component	Built-in component/connector

Material

Housing material	Polyamide
Halogen free	Yes
Contact material	CuZn
Insulation components continous temperature	100 °C
Surface finish	Silver-plated

Dimensions

Length	44.6 mm
Width	35 mm
Height	35 mm

Technical drawing

