



Product data sheet

Item No. 96.050.0153.1

Distributor RST20I5B 3P1 F VG SW

RST compact distributer RST20i5, 5 pole, 1 input, 3 outputs, with mounting option, 250/400V, 20A, color of coding: black



| Item No. | 96.050.0153.1 |
|------------|---------------|
| EAN | 4015573936454 |
| Order Unit | 1 Piece(s) |

Certificates / Approvals



Technical data

General

| Rated current | 20 A |
|---|------------|
| Rated voltage | 250 V |
| - | |
| Rated voltage 2 | 400 V |
| Rated impulse voltage | 4 kV |
| Pollution degree | 3 |
| Mechanical coding | Code 0 |
| Lockable | Yes |
| Color of coding/ contact carrier | Black |
| Color of separate housing (only for modular versions) | Light grey |

Model

| Number of inputs | 1 |
|---------------------------|-----------------------------|
| Number of outputs | 3 |
| Type of fastening | Yes |
| Degree of protection (IP) | IP66/68 (3m;2h) /IP69 |
| Type of distributor | Combined distribution block |





Material

| Housing material | Polyamide |
|---|---------------|
| Halogen free | Yes |
| Contact material | CuZn |
| Insulation components continous temperature | 100 °C |
| Surface finish | Silver-plated |

Dimensions

| Length | 162 mm |
|--------|---------|
| Width | 104 mm |
| Height | 57.2 mm |

Technical drawing

