



Product data sheet

Item No. 96.051.5053.6

Device connector RST20I5S B1 M01 A TB0

RST 20i5/4 device connection M25, 5 pole, female, screw connection, application 250V, 20A, coding-color turquoise blue, color of housing black



Item No.	96.051.5053.6
EAN	4015573877542
Order Unit	100 Piece(s)

Certificates / Approvals











General

Rated current	20 A
Rated voltage	250 V
Pollution degree	3
Mechanical coding	Code 4
Rated impulse voltage	4 kV
Continuity resistor	3 mOhm
Lockable	Yes
Color of coding/ contact carrier	Turquoise
Marking of poles	D1, D2, L, PE, N

Connection Data

Cross section solid	4 mm²
Cross section solid 2	0.75 mm²
Connection cross section stranded (max.)	4 mm²
Cross section stranded 2	0.75 mm²
Terminations per pole	1
Wire strip length	8 mm





Model

Model	female
Connection type	Screw connection
Connecting thread metric	M25
Angle of plug	Straight
Inclination	0 °
Degree of protection (IP)	IP66/68 (3m;2h) /IP69
Thickness of housings (electrical device) 2	0.5 mm
Thickness of housings (electrical device)	8 mm
Built-in component	Built-in component/connector

Material

Housing material	Polyamide
Halogen free	Yes
Contact material	CuZn
Insulation components continous temperature	100 °C
Surface finish	Silver-plated

Dimensions

Length	51.3 mm
Width	35 mm
Height	35 mm

Technical drawing

