



# Product data sheet

Item No. 96.152.1053.1

## Device connector RST20I5C S1 M01V SW

RST 20i5/4 device connection M25, 5 pole, male, for crimpcontact, application 250V/400V, 20A, coding-color black, color of housing black



Item No.	96.152.1053.1
EAN	4015573933750
Order Unit	100 Piece(s)

# Certificates / Approvals



## Technical data

### General

Rated current	20 A
Rated voltage	250 V
Rated voltage 2	400 V
Pollution degree	3
Mechanical coding	Code 0
Rated impulse voltage	4 kV
Continuity resistor	3 mOhm
Lockable	Yes
Color of coding/ contact carrier	Black
Marking of poles	1, 2, 3, N, PE

### **Connection Data**

Cross section solid	4 mm²
Connection cross section stranded (max.)	4 mm²
Cross section stranded 2	0.75 mm²
Terminations per pole	1
Wire strip length	7 mm





### Model

Model	male
Connection type	Crimp
Connecting thread metric	M25
Angle of plug	Straight
Inclination	0 °
Degree of protection (IP)	IP66/68 (3m;2h) /IP69
Thickness of housings (electrical device) 2	0.5 mm
Thickness of housings (electrical device)	8 mm
Built-in component	Built-in component/connector

#### Material

Housing material	Polyamide
Halogen free	Yes
Contact material	CuZn
Insulation components continous temperature	100 °C
Surface finish	Silver-plated

#### Dimensions

Length	42 mm
Width	35 mm
Height	35 mm

## Technical drawing

