



Product data sheet

Item No. 96.152.2053.1

Device connector RST20I5C S1 M00V SW

RST 20i5/4 device connection M20, 5 pole, male, for crimpcontact, modular, application 250V/400V, 20A, coding-color black, color of housing black



Item No.	96.152.2053.1
EAN	4015573933712
Order Unit	100 Piece(s)

Certificates / Approvals



Technical data

General

General	
Rated current	20 A
Rated voltage	250 V
Rated voltage 2	400 V
Pollution degree	3
Mechanical coding	Code 0
Rated impulse voltage	4 kV
Continuity resistor	3 mOhm
Lockable	Yes
Color of coding/ contact carrier	Black
Marking of poles	1, 2, 3, N, PE
Color of separate adapter (if present)	Black

Connection Data

Cross section solid	4 mm²
Connection cross section stranded (max.)	4 mm²
Cross section stranded 2	0.75 mm²
Terminations per pole	1
Wire strip length	7 mm





Model

Model	male
Connection type	Crimp
Connecting thread metric	M20
Angle of plug	Straight
Inclination	0 °
Degree of protection (IP)	IP66/68 (3m;2h) /IP69
Thickness of housings (electrical device) 2	0.5 mm
Thickness of housings (electrical device)	8 mm
Built-in component	Built-in component/connector

Material

Housing material	Polyamide
Halogen free	Yes
Contact material	CuZn
Insulation components continous temperature	100 °C
Surface finish	Silver-plated

Dimensions

Length	66.2 mm
Width	35 mm
Height	35 mm

Technical drawing

