



Product data sheet

Item No. 96.452.1003.6

Cable assembly RST20I5KSB- 15P 10TB0

RST 20i5/4 connection cable female - free end, 5 pole, assembled with screw connection, application 250V, 16A, cable type H05VV-F, length 1.0m, cross section 1,5mm², coding-color turquoise blue



Item No.	96.452.1003.6
EAN	4015573941854
Order Unit	30 Piece(s)

Certificates / Approvals



Technical data

General

Rated current	16 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Pollution degree	3
Mechanical coding	Code 4
Continuity resistor	3 mOhm
Lockable	Yes
Color of coding/ contact carrier	Turquoise
Marking of poles	D1, D2, L, PE, N
Color of housing inclusive strain relief	Black

Model

type of construction	Cable screw gland
Nominal cross section conductor	1.5 mm ²
Degree of protection (IP)	IP66/68 (3m;2h) /IP69
Wire strip length	9 mm
sheath strip length	35 mm
Preparation of conductor ends	Ultrasonically compressed wire ends





Cable type	H05VV-F
Cable colour	Black
Cable diameter	10.1 mm
Version of cable	Female - free end
Type of cord set	Connection cable
Version cable end 1	female
Version cable end 2	Free end

Material

Surface finish	Silver-plated
Halogen free	No
Continuous temperature of cable	70 °C
Insulation components continous temperature	100 °C

Dimensions

Total langth	4	
Total length	1 m	

Technical drawing

