

Product data sheet

Item No. 96.453.4004.1

Cable assembly RST20I5KS-S 25P 40SW

RST 20i5/4 connection cable male - free end, 5 pole, assembled with screw connection, application 250V/400V, 20A, cable type H05VV-F, length 4.0m, cross section 2,5mm², coding-color black



Item No.	96.453.4004.1
EAN	4015573919181
Order Unit	10 Piece(s)

Certificates / Approvals



Technical data

General

Rated current	20 A
Rated voltage	250 V
Rated voltage 2	400 V
Rated impulse voltage	4 kV
Pollution degree	3
Mechanical coding	Code 0
Continuity resistor	3 mOhm
Lockable	Yes
Color of coding/ contact carrier	Black
Marking of poles	1, 2, 3, N, PE
Color of housing inclusive strain relief	Black

Model

type of construction	Cable screw gland
Nominal cross section conductor	2.5 mm ²
Degree of protection (IP)	IP66/68 (3m;2h) /IP69
Wire strip length	9 mm
sheath strip length	35 mm



Preparation of conductor ends	Ultrasonically compressed wire ends
Cable type	H05VV-F
Cable colour	Black
Cable diameter	12.1 mm
Version of cable	Male - free end
Type of cord set	Connection cable
Version cable end 1	Free end
Version cable end 2	male

Material

Surface finish	Silver-plated
Halogen free	No
Continuous temperature of cable	70 °C
Insulation components continuous temperature	100 °C

Dimensions

Total length	4 m
--------------	-----

Technical drawing

Kabeltype/cable type H05VV-F5G2,5

Kodierung/keying 0
(250V/20A)

Z

Farbe/color		.F
schwarz/black		.1
lichtgrau/light grey		.0
Teile-Nr. part-no.	L	Beispiel (Farbe: schwarz, lichtgrau) Typ (example (colour: black, grey) type
96.453.XX04.1	XX in dm-Schritten	96.453.1004.1 = 10dm/L=1000mm RST201SKS-S 25P 10SW
96.453.XX04.0		96.453.1204.0 RST201SKS-S 25P 10BL
96.453.XX04.1	XX in m-Schritten	96.453.1204.1 = 12 m/L=12000mm RST201SKS-S 25P X12SW
96.453.XX04.0		96.453.1204.0 RST201SKS-S 25P X12BL
<small> For further information please refer to the data sheet. (For further information please refer to the data sheet.) Die in der Tabelle aufgeführten Werte sind die Nennwerte. (The values in the table are the nominal values.) Die in der Tabelle aufgeführten Werte sind die Nennwerte. (The values in the table are the nominal values.) Die in der Tabelle aufgeführten Werte sind die Nennwerte. (The values in the table are the nominal values.) </small>		
Technische Zeichnung/Technical drawing 1:1		Datum/Date: 10.05.2010 Zeichnung Nr./Drawing No.: 96.453.1004.0 01K Blatt 1 von 1/Sheet 1 of 1
		KONFEKT-LEITUNG Konfektions- und Montageanleitung Konfektions- und Montageanleitung Konfektions- und Montageanleitung