



Representative Image

Ref. No. 672568 | Cat. No. CAS/H

Description: Adjustable Auxiliary Contact CA S/H

EAN 5413656725688

Home > Modular DIN-rail devices > Add-on devices and accessories

Descriptors

Category | Add-on devices and accessories

Specifications

Series	Auxiliaries for automatic switches
Range	Auxiliary - Series CA
Function	Auxiliary/signal contact
Rated current In	5 A
Number of modules	1/2
Standard packing	1
Standards	CE, EN 62019
Electrical service life	10000
Minimum operating voltage U _{bmin} (V)	24 V
Contact combination	1 interchangeable contact
Terminal capacity (mm ²)	2.5 mm ²
Electrical endurance (ms)	10000

Classifications

Approvals	CEBEC, IMQ, KEMA, NF, VDE
ETIM 5.0	EC000041
ETIM 6.0	EC000041

Dimensions

Weight | 0.070 kg

Publications

Title	Publication No.	Publication Type
Add-on device - Series CA/CA UN - Auxiliary Contact CA S/H (pdf) 3D PDF Viewer: Modular DIN-rail device - Add-on device - Series CA/CA UN - Auxiliary Contact CA S/H (3DPDF format)	3D-01059-PDF	Drawings - CAD - 3D
Add-on device - Series CA/CA UN - Auxiliary Contact CA S/H (stp) 3D Drawing: Modular DIN-rail device - Add-on device - Series CA/CA UN - Auxiliary Contact CA S/H (STEP format)	3D-01059	Drawings - CAD - 3D

Additional Documentation: Visit our [Publication Library](#) to find technical documentation, specifications, catalogues, promotional literature, 3D's,...