

Sealing grommet

Ethylene-Propylene rubber EPDM

### Properties

- "Pushout"-membrane
- easy-to-install without the use of tools
- less material makes it easier to install, as well as pull out
- wide sealing range
- halogen-free
- can be installed from either end depending on application
- soft and adaptable, can therefore also be used on curved surfaces

Temperature range

-40 °C / +110 °C  
(static, unstressed)

Protection grade

IP67

Test standard

EN 60670-1:2005+A1:2013

SEMKO report

1313520

### Features



RAL 9005

Size	Hole / Di	Wall / T	ØC	L1	H	Da	<input type="checkbox"/>	Part No.
M16	16,5	1 - 4	5 - 9	11	18	21	50	G503-1016-02
M20	20,5	1 - 4	8 - 12	13,4	20	25,5	50	G503-1020-02
M25	25,5	1 - 4	11 - 16	15,3	21,6	30,5	50	G503-1025-02



RAL 7035

Size	Hole / Di	Wall / T	ØC	L1	H	Da	<input type="checkbox"/>	Part No.
M16	16,5	1 - 4	5 - 9	11	18	21	50	G503-1016-01
M20	20,5	1 - 4	8 - 12	13,4	20	25,5	50	G503-1020-01

Size	Hole / Di	Wall / T	ØC	L1	H	Da	<input type="checkbox"/>	Part No.
------	-----------	----------	----	----	---	----	--------------------------	----------

M25    25,5    1 - 4    11 - 16    15,3    21,6    30,5    50    G503-1025-01

RAL 7001

Size	Hole / Di	Wall / T	ØC	L1	H	Da	<input type="checkbox"/>	Part No.
------	-----------	----------	----	----	---	----	--------------------------	----------

M16    16,5    1 - 4    5 - 9    11    18    21    50    G503-1016-00

M20    20,5    1 - 4    8 - 12    13,4    20    25,5    50    G503-1020-00

M25    25,5    1 - 4    11 - 16    15,3    21,6    30,5    50    G503-1025-00