

Product data sheet

Item No. 91.932.3053.0

Male connector with strain relief GST15i3S S1 ZR1W
WS

Connector GST15i3, 3 pole, male, screw connection, 250V/16A,
color of coding: white, color of housing: white



Item No.	91.932.3053.0
EAN	4015573833838
Order Unit	100 Piece(s)

Certificates / Approvals



Technical data

General

Rated current	16 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Strain relief	Yes
Pollution degree	2
Mechanical coding	Code 1
Lockable	Yes
Color of coding/ contact carrier	White
Marking of poles	L, N, PE
Color of housing inclusive strain relief	White

Connection Data

Cable diameter	9 mm
Cable diameter 2	5.5 mm
Cross section solid	2.5 mm ²
Cross section solid 2	0.5 mm ²
Connection cross section stranded max.	2.5 mm ²
Cross section stranded 2	0.5 mm ²

Terminations per pole	1
-----------------------	---

Model

Model	male
Connection type	Screw connection
Degree of protection (IP)	IP20

Material

Housing material	Polyamide
Halogen free	Yes
Contact material	CuZn
Insulation components continuous temperature	100 °C
Surface finish	Silver-plated

Dimensions

Length	53.2 mm
Width	23 mm
Height	13.8 mm

Technical drawing

Ansicht / view X

23

53,2

13,8

zusammengebaut complete

M 1:1

Teile-Nr./ part no.:	Material:	Farbe/ colour:
91.932.3053.0	PA UL94-V0 halogenfrei/ halogen-free	weiß/ white
91.932.3053.1	PA UL94-V0 halogenfrei/ halogen-free	schwarz/ black

Wieland
Elektrotechnik
Verbindungen

STECKERT_M_ZUGENTL
mate connector with strain relief 250V 16A