



# Product data sheet

Item No. 96.032.5053.1

### Device connector RST20I3S S1 M01V SW

RST 20i3/2 device connection M25, 3 pole, male, screw connection, application 250V, 20A, coding-color black, color of housing black



| Item No.   | 96.032.5053.1 |
|------------|---------------|
| EAN        | 4015573793262 |
| Order Unit | 100 Piece(s)  |

# Certificates / Approvals











# Technical data

### General

| Rated current                    | 20 A     |
|----------------------------------|----------|
| Rated voltage                    | 250 V    |
| Pollution degree                 | 3        |
| Mechanical coding                | Code 0   |
| Rated impulse voltage            | 4 kV     |
| Continuity resistor              | 3 mOhm   |
| Lockable                         | Yes      |
| Color of coding/ contact carrier | Black    |
| Marking of poles                 | L, N, PE |

## **Connection Data**

| Cross section solid                      | 6 mm²    |
|--|----------|
| Cross section solid 2                    | 0.75 mm² |
| Connection cross section stranded (max.) | 6 mm²    |
| Cross section stranded 2                 | 0.75 mm² |
| Terminations per pole                    | 1        |
| Wire strip length                        | 8 mm     |





#### Model

| Model                                       | male                         |
|---|------------------------------|
| Connection type                             | Screw connection             |
| Connecting thread metric                    | M25                          |
| Angle of plug                               | Straight                     |
| Inclination                                 | 0 °                          |
| Degree of protection (IP)                   | IP66/68 (3m;2h) /IP69        |
| Thickness of housings (electrical device) 2 | 0.5 mm                       |
| Thickness of housings (electrical device)   | 8 mm                         |
| Built-in component                          | Built-in component/connector |

#### Material

| Housing material                            | Polyamide     |
|---|---------------|
| Halogen free                                | Yes           |
| Contact material                            | CuZn          |
| Insulation components continous temperature | 100 °C        |
| Surface finish                              | Silver-plated |

#### Dimensions

| Length | 44.6 mm |
|--------|---------|
| Width  | 35 mm   |
| Height | 35 mm   |

## Technical drawing

