

Product data sheet

Item No. 96.051.4353.6

Connector RST20i5S B1 ZRYS A TB04

RST 20i5/4 splitter connector, 5 pole, screw connection, application 250V, 20A, for cable diameters 10-14mm, coding-color turquoise blue, color of housing black



Item No.	96.051.4353.6
EAN	4015573936584
Order Unit	100 Piece(s)

Certificates / Approvals



Technical data

General

Rated current	20 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Strain relief	Yes
Pollution degree	3
Mechanical coding	Code 4
Lockable	Yes
Color of coding/ contact carrier	Turquoise
Marking of poles	D1, D2, L, PE, N
Color of housing inclusive strain relief	Black

Connection Data

Cable diameter	14 mm
Cable diameter 2	10 mm
Cable diameter 3	14 mm
Cross section solid	1.5 mm ²
Cross section solid 2	0.75 mm ²
Connection cross section stranded max.	1.5 mm ²

Cross section stranded 2	0.75 mm ²
Terminations per pole	1
Connection cross section stranded min.	0.75 mm ²
Connection cross section stranded max.	1.5 mm ²

Model

Model	female
Connection type	Screw connection
Degree of protection (IP)	IP66/68 (3m,2h) /IP69

Material

Housing material	Polyamide
Halogen free	Yes
Contact material	CuZn
Insulation components continuous temperature	100 °C
Surface finish	Silver-plated

Dimensions

Length	96 mm
Width	59 mm
Height	38 mm

Technical drawing

Auslieferungszustand delivery status

für Kabeldurchm. 10-14mm
for cable diameter 10-14mm
Farbe: schwarz, öhnl. RAL 9005
color: black, similar to RAL 9005

Farbe: türkisblau, öhnl. RAL 5018
color: turquoise blue, similar to RAL 5018

Type: RST2015S B1 ZRYSVA TB04

Verpackungseinheit: je 100 Stück
packaging unit: per 100

960514353601K_2 CADW3029 Schmitt 2014-12-16T09:54:57 21.000

BUCHSENTE I L_M_DOPPELZUGENTL
female connector with double cord grip
Schraubanschluß/screw connection
Kabelierung /cabling z. 1200V/250V/20A