

Product data sheet

Item No. 96.232.0534.1

Cable assembly RST20i3K1-S 15 05SW

RST 20i3/2 connection cable male - free end, 3 pole, assembled with shrinkage tube, application 250V, 16A, cable type H07RN-F, length 0.5m, cross section 1.5mm², coding-color black



Item No.	96.232.0534.1
EAN	4015573851986
Order Unit	75 Piece(s)

Certificates / Approvals



Technical data

General

Rated current	16 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Pollution degree	3
Mechanical coding	Code 0
Continuity resistor	3 mOhm
Lockable	Yes
Color of coding/ contact carrier	Black
Marking of poles	L, N, PE
Color of housing inclusive strain relief	Black

Model

type of construction	Shrinkage tube
Nominal cross section conductor	1.5 mm ²
Degree of protection (IP)	IP66/68 (3m;2h)
Wire strip length	9 mm
sheath strip length	35 mm
Preparation of conductor ends	Ultrasonically compressed wire ends

Cable type	H07RN-F
Cable colour	Black
Cable diameter	9.8 mm
Version of cable	Male - free end
Type of cord set	Connection cable
Version cable end 1	Free end
Version cable end 2	male
Screened	No

Material

Surface finish	Silver-plated
Halogen free	No
Continuous temperature of cable	60 °C
Insulation components continuous temperature	100 °C

Dimensions

Total length	0.5 m
--------------	-------

Technical drawing

Farbe/colour

schwarz/black	.1
lichtgrau/light grey	.0
betongrau/concrete grey	.3

Teile-Nr. part - no.	L	Beispiel (Farbe: schwarz, lichtgrau) example (colour: black, light grey)	Typ type
96.232.XX34.1	XX in dm-Schritten	96.232.1034.1 = 10dm/L = 1000mm	RST2013K1-S 15 10SW
96.232.XX34.0		96.232.1034.0	RST2013K1-S 15 10GL
U6.232.XX34.1	XX in m-Schritten	U6.232.1234.1 = 12 m/L=12000mm	RST2013K1-S 15 X12SW
U6.232.XX34.0		U6.232.1234.0	RST2013K1-S 15 X12GL

Freioleranz nach General tolerance: 2007 Typ/Date Name: 22.02. Meitz T Zeichnung Nr./Drawing No.: 96.232.0434.0 01K a

www.wieland.com

KONFEKT-LEITUNG
freies Ende-Stecker Crimpausführung/free-end male pre-assembled cable crimp design K1 250V