

Product data sheet

Item No. 96.232.3033.1

Cable assembly RST20I3K1B- 15 30SW

RST 20i3/2 connection cable female - free end, 3 pole, assembled with shrinkage tube, application 250V, 16A, cable type H07RN-F, length 3.0m, cross section 1.5mm², coding-color black



Item No.	96.232.3033.1
EAN	4015573761742
Order Unit	20 Piece(s)

Certificates / Approvals



Technical data

General

Rated current	16 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Pollution degree	3
Mechanical coding	Code 0
Continuity resistor	3 mOhm
Lockable	Yes
Color of coding/ contact carrier	Black
Marking of poles	L, N, PE
Color of housing inclusive strain relief	Black

Model

type of construction	Shrinkage tube
Nominal cross section conductor	1.5 mm ²
Degree of protection (IP)	IP66/68 (3m;2h)
Wire strip length	9 mm
sheath strip length	35 mm
Preparation of conductor ends	Ultrasonically compressed wire ends

Cable type	H07RN-F
Cable colour	Black
Cable diameter	9.8 mm
Version of cable	Female - free end
Type of cord set	Connection cable
Version cable end 1	female
Version cable end 2	Free end
Screened	No

Material

Surface finish	Silver-plated
Halogen free	No
Continuous temperature of cable	60 °C
Insulation components continuous temperature	100 °C

Dimensions

Total length	3 m
--------------	-----

Technical drawing

Buchse, Farbe .1/.0
Female connector, colour .1/.0

Kabel H07RN-F 3G1,5 SW
cable H07RN-F 3G1,5 black

1.5" max 16A
V91 xov „5“ i

ca. 82

L ± 3%

Gesamtlänge/totale length

Farbe/colour
schwarz/black .1
lichtgrau/light grey .0

Teile-Nr. part -no.	L	Beispiel (Farbe: schwarz, lichtgrau) example (colour: black, light grey)	Typ type
96.232.XX33.1	XX in dm-Schritten	96.232.1033.1 = 10dm/L = 1000mm	RST2013K1B- 15 10SW
96.232.XX33.0		96.232.1033.0	RST2013K1B- 15 10GL
U6.232.XX33.1	XX in m-Schritten	U6.232.1233.1 = 12 m/L=12000mm	RST2013K1B- 15 X12SW
U6.232.XX33.0		U6.232.1233.0	RST2013K1B- 15 X12GL

Freitoleranz nach ISO 14405 (Tolerance system Size ISO 14405) / Drawing, no manual modifications allowed

Werkstoff/Material: 2007 Typ/Ste Name: T Zeichnung Nr./Drawing No.: 96.232.0433.0 01K b

www.wieland.com

KONFEKT-LEITUNG
Buchse-freies Ende Crimpausführung/female-free end pre-assembled cable crimp design K1 250V