

Product data sheet

Item No. 96.452.4004.6

Cable assembly RST20i5KS-S 15P 40TB0

RST 20i5/4 connection cable male - free end, 5 pole, assembled with screw connection, application 250V, 16A, cable type H05VV-F, length 4.0m, cross section 1,5mm<sup>2</sup>, coding-color turquoise blue



Item No.	96.452.4004.6
EAN	4015573941960
Order Unit	10 Piece(s)

Certificates / Approvals



Technical data

**General**

Rated current	16 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Pollution degree	3
Mechanical coding	Code 4
Continuity resistor	3 mOhm
Lockable	Yes
Color of coding/ contact carrier	Turquoise
Marking of poles	D1, D2, L, PE, N
Color of housing inclusive strain relief	Black

**Model**

type of construction	Cable screw gland
Nominal cross section conductor	1.5 mm <sup>2</sup>
Degree of protection (IP)	IP66/68 (3m;2h) /IP69
Wire strip length	9 mm
sheath strip length	35 mm
Preparation of conductor ends	Ultrasonically compressed wire ends



Cable type	H05VV-F
Cable colour	Black
Cable diameter	10.1 mm
Version of cable	Male - free end
Type of cord set	Connection cable
Version cable end 1	Free end
Version cable end 2	male

Material

Surface finish	Silver-plated
Halogen free	No
Continuous temperature of cable	70 °C
Insulation components continuous temperature	100 °C

Dimensions

Total length	4 m
--------------	-----

Technical drawing

