

**Product data sheet**
**Item No. 96.452.5000.6**
**Cable assembly RST20i5KSBS 15P 50TB0**

 RST 20i5/4 extension cable female - male, 5 pole, assembled with screw connection, application 250V, 16A, cable type H05VV-F, length 5.0m, cross section 1,5mm<sup>2</sup>, coding-color turquoise blue


Item No.	96.452.5000.6
EAN	4015573941816
Order Unit	10 Piece(s)

**Certificates / Approvals**

**Technical data**
**General**

Rated current	16 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Pollution degree	3
Mechanical coding	Code 4
Continuity resistor	3 mOhm
Lockable	Yes
Color of coding/ contact carrier	Turquoise
Marking of poles	D1, D2, L, PE, N
Color of housing inclusive strain relief	Black

**Model**

type of construction	Cable screw gland
Nominal cross section conductor	1.5 mm <sup>2</sup>
Degree of protection (IP)	IP66/68 (3m;2h) /IP69
Cable type	H05VV-F
Cable colour	Black
Cable diameter	10.1 mm



Version of cable	Female - male
Type of cord set	Extension cable
Version cable end 1	female
Version cable end 2	male

**Material**

Surface finish	Silver-plated
Halogen free	No
Continuous temperature of cable	70 °C
Insulation components continuous temperature	100 °C

**Dimensions**

Total length	5 m
--------------	-----

**Technical drawing**

Kabeltype/cable type H05VV-F5G1,5

Teil-Nr. / part-no.	L	Beispiel (Farbe: türkisblau) / example (colour: turquoise)	Typ / type
96.452.XX00.6	XX in dm-Schritten	96.452.1000.6 = 10dm/L = 1000mm	RS120/SK385 15P 107B04
US.452.XX00.6	XX in m-Schritten	US.452.1000.6 = 12 m/L = 12000mm	RS120/SK385 15P X127B04

Part No.	Part Name	Part Description	Part Drawing	Part Status
96.452.1000.6	KONFEKT_LEITUNG	5-core extension cable	96.452.1000.6 01K a	Released