

Product data sheet
Item No. 96.453.2000.6
Cable assembly RST20I5KSBS 25P 20TB0

 RST 20i5/4 extension cable female - male, 5 pole, assembled with screw connection, application 250V, 20A, cable type H05VV-F, length 2.0m, cross section 2,5mm², coding-color turquoise blue


Item No.	96.453.2000.6
EAN	4015573941625
Order Unit	15 Piece(s)

Certificates / Approvals

Technical data
General

Rated current	20 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Pollution degree	3
Mechanical coding	Code 4
Continuity resistor	3 mOhm
Lockable	Yes
Color of coding/ contact carrier	Turquoise
Marking of poles	D1, D2, L, PE, N
Color of housing inclusive strain relief	Black

Model

type of construction	Cable screw gland
Nominal cross section conductor	2.5 mm ²
Degree of protection (IP)	IP66/68 (3m;2h) /IP69
Cable type	H05VV-F
Cable colour	Black
Cable diameter	12.1 mm



Version of cable	Female - male
Type of cord set	Extension cable
Version cable end 1	female
Version cable end 2	male

Material

Surface finish	Silver-plated
Halogen free	No
Continuous temperature of cable	70 °C
Insulation components continuous temperature	100 °C

Dimensions

Total length	2 m
--------------	-----

Technical drawing

Kabeltype/cable type H05VV-F562,5

Teil-Nr. part-no.	L	Beispiel (Farbe: türkisblau) example (colour: turquoise)	Typ type
96.453.XX00.6	XX in dm-Schritten	96.453.1000.6 = 10dm/L = 1000mm	RS120/56385 25P 107B04
US.453.XX00.6	XX in m-Schritten	US.453.1000.6 = 12 m/L = 12000mm	RS120/56385 25P X127B04

Code	Symbol	Value	Unit
1	1	96.453.1000.6	01K a

wieland
Konfekt-Leitung