

<b>FDV – DOKUMENTASJON</b>		<b>Nr.:102</b>
		<b>Rev.:</b>
		<b>Dato: 31.10.2016</b>
<b>Produktspesifikasjon</b>	PERFECT EMC-cable gland PG	
<b>Produktnavn</b>	50.0xx/EMV	
<b>Anvisning for drift</b>	Ingen anvisning for drift	
<b>Vedlikehold</b>	Ingen vedlikehold	
<b>Henvisninger Vedlegg</b>	Datablad	
<b>Produsent</b>	<b>Jacob GmbH</b> <b>Elektrotechnische Fabrik</b> Gottlieb-Daimler-Strasse 11 D-71394 Kernen Germany	
<b>Importør</b>	<b>EFA Elektro AS,</b> Postboks 593, 1411 Kolbotn, Norway Tlf. 66812400 e-mail: post@efa.no - <b>www.efa.no</b>	

## PERFECT EMC-cable gland

50.0xx/EMV

Dome nut	Brass CuZn39Pb3, nickel-plated
Lamellar insert	Polyamide PA6 V-2
Sealing ring	Polychloroprene-Nitrile rubber CR/NBR
Gland body	Brass CuZn39Pb3, nickel-plated
O-ring	Nitrile rubber NBR
Connecting thread	Pg as per DIN 40430



### Properties

	<ul style="list-style-type: none"> <li>• for cables with shielding</li> <li>• integrated anchorage</li> <li>• protection against twisting,</li> <li>• wide sealing and clamping range</li> </ul>
Temperature range (°C)	-20°C / +100°C (dynamic) -40°C (static, short term)
Protection grade	68 5

